

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 10/3/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Rum (Ethanol Solution) between 24% and 70% vol

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Alcoholic beverages, Odour agents,

1.3. Supplier

E&A Scheer B.V.
Herengracht 316
Amsterdam, 1016 CD
The Netherlands
T +31 (0)20 624 34 12 - F +31 (0)20 622 09 76
info@rum.nl - www.rum.nl

1.4. Emergency telephone number

Toll Free: 1-800-424-9300 | Local: +1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2 H225 Highly flammable liquid and vapor Serious eye damage/eye irritation Category 2 H319 Causes serious eye irritation Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use media other than water to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	GHS US classification
ethanol, ethyl alcohol	CAS-No.: 64-17-5		Flam. Liq. 2, H225 Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical

advice/attention if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove contaminated clothes. If skin irritation or rash occurs: Get

medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

10/3/2024 (Issue date) EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor. Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : For further information, refer to section 10 : "Stability and Reactivity".

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Other information : Prevent fire-fighting water from entering environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Emergency procedures : Ventilate area.

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see item 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

No additional information available

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Heat-ignition : Keep away from heat and direct sunlight.

Packaging materials : Store in glass, stainless steel, plastic or epoxy lined receptacles. Unsuitable materials: copper,

Aluminum.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol, ethyl alcohol (64-17-5)				
USA - ACGIH - Occupational Exposure Limits				
Local name	Ethanol			
ACGIH OEL STEL	1000 ppm			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethanol, ethyl alcohol (64-17-5)			
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)		
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans		
Regulatory reference	ACGIH 2024		
USA - OSHA - Occupational Exposure Limits			
Local name	Ethyl alcohol (Ethanol)		
OSHA PEL TWA	1900 mg/m³		
	1000 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
USA - IDLH - Occupational Exposure Limits			
IDLH	3300 ppm (10% LEL)		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL (TWA)	1900 mg/m³		
	1000 ppm		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Safety glasses.

Hand protection:

In case of repeated or prolonged contact wear gloves. Polyvinylchloride (PVC). 0.11 mm. ISO 374-1

Eye protection:

Safety glasses. DIN EN 166

Skin and body protection:

Wear suitable protective clothing. CEN: EN 340; EN 369; EN 465

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection. EN 143

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : various colors
Odor : characteristic
Odor threshold : No data available

pH : 4 – 8.5

Melting point : -130 - -112 °C Freezing point : No data available

Boiling point : > 78.3 °C Flash point : > 21 °C (70%)

35 %vol. 27,5°C 40 %vol. 26°C 45 %vol. 25°C 50 %vol. 24°C 55 %vol. 23°C 60 %vol. 22°C 65 %vol. 21,5°C 70 %vol. 21°C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : 3.3 – 19 % v/v

Relative vapor density at 20°C : 59

Relative density : 35 %vol. 0,95559

40 %vol. 0,94805 45 %vol. 0,93954 55 %vol. 0,91996 60 %vol. 0,90911 65 %vol. 0,88765 70 %vol. 0,88556 Soluble in water.

Solubility : Soluble in water.
Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : 363 °C

Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits : No data available Explosive properties : No data available Oxidizing properties : No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10/3/2024 (Issue date) EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Extremely high or low temperatures. Keep out of direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

1	ľ		ln:	fr	rn	าล	tic	'n	on	1	O.	γi	CO	In	ai	ica	م ا	ff	20	te	2	
					,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ш		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	OI	_		AH.		ш	101	u		•	eu	-	-	

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

	,			
ethanol, ethyl alcohol (64-17-5)				
LD50 oral rat	7060 mg/kg (Source: NLM_CIP)			
LD50 oral	10470 mg/kg body weight			
LD50 dermal	15800 mg/kg body weight			
LC50 Inhalation - Rat	133.8 mg/l/4h			
LC50 Inhalation - Rat (Dust/Mist)	> 99999 mg/l			
ATE US (oral)	7060 mg/kg body weight			
ATE US (dermal)	15800 mg/kg body weight			
ATE US (vapors)	133.8 mg/l/4h			
ATE US (dust, mist)	133.8 mg/l/4h			
Ckin correction/irritation	· Net described (Peaced on excitable data, the algorification criteria are not met)			

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: 4 – 8.5

Serious eye damage/irritation : Causes serious eye irritation.

pH: 4 - 8.5

Respiratory or skin sensitization : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

ethanol	. ethy	alcohol	(64-17-5)
otilalio	,	i diooiloi	(04 11 0)

 IARC group
 1 - Carcinogenic to humans

 Reproductive toxicity
 : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Viscosity, kinematic : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

ethanol, ethyl alcohol (64-17-5)				
LC50 - Fish [1]	14200 mg/l			
EC50 - Crustacea [1]	5463 mg/l			
EC50 - Other aquatic organisms [1]	5012 mg/l waterflea			
EC50 - Other aquatic organisms [2]	275 mg/l			
ErC50 algae	1000 mg/l			
NOEC chronic crustacea	9.6 mg/l			

12.2. Persistence and degradability

Rum (Ethanol Solution) between 24% and 70% vol				
Persistence and degradability	Not established.			
ethanol, ethyl alcohol (64-17-5)				
Persistence and degradability	Readily biodegradable.			

12.3. Bioaccumulative potential

Rum (Ethanol Solution) between 24% and 70% vol				
Bioaccumulative potential	Not established.			
ethanol, ethyl alcohol (64-17-5)				
Partition coefficient n-octanol/water (Log Pow) -0.32				

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations

Additional information

: Dispose in a safe manner in accordance with local/national regulations.

: Empty containers should be taken for recycling, recovery or waste in accordance with local

regulation. Flammable vapors may accumulate in the container.

Ecological waste information : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

10/3/2024 (Issue date) EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3065	UN3065	3065	3065
14.2. Proper Shipping Name			
Alcoholic beverages	ALCOHOLIC BEVERAGES	ALCOHOLIC BEVERAGES	Alcoholic beverages
Transport document description			
UN3065 Alcoholic beverages, 3, III UN3065 ALCOHOLIC BEVERAGES, 3, III		UN 3065 ALCOHOLIC BEVERAGES, 3, III	UN 3065 Alcoholic beverages, 3, III
14.3. Transport hazard class(es	5)		
3	3	3	3
FLAMMABLE LIQUID	3	3	3
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available	ble		1

14.6. Special precautions for user

DOT

UN-No.(DOT)

: UN3065

DOT Special Provisions (49 CFR 172.102)

: 24 - Alcoholic beverages containing more than 70 percent alcohol by volume must be transported as materials in Packing Group II. Alcoholic beverages containing more than 24 percent but not more than 70 percent alcohol by volume must be transported as materials in Packing Group III.

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

N11 - This material is excepted for the specification packaging requirements of this subchapter if the material is packaged in strong, tight non-bulk packaging meeting the requirements of subparts A and B of part 173 of this subchapter.

T2 - 1.5 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

: 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

TDG

UN-No. (TDG) : UN3065
Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E1
Passenger Carrying Road Vehicle or Passenger : 60 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 127

IMDG

Special provision (IMDG) : 144, 145, 247

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001

Packing provisions (IMDG) : PP2

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T2

Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

Stowage category (IMDG) : A

Properties and observations (IMDG) : Alcoholic beverages containing

Alcoholic beverages containing more than 24% alcohol but not more than 70% by volume, when transported as part of the manufacturing process, may be transported in wooden barrels with a capacity of more than 250 litres and not more than 500 litres meeting the general requirements of 4.1.1, as appropriate, on the following conditions: 1. the wooden barrels should be checked and tightened before filling; 2. sufficient ullage (not less than 3%) should be left to allow for the expansion of the liquid; 3. the wooden barrels should be transported with the bungholes pointing upwards; 4. the wooden barrels should be transported in containers meeting the requirements of the International Convention for Safe Containers (CSC), as amended. Each wooden barrel should be secured in custom-made cradles and should be wedged by appropriate means to prevent them from being displaced in any way during transport; and 5. when carried on board ships, the containers should be stowed in open cargo spaces or in enclosed cargo spaces complying with the requirements for class 3 flammable liquids with a flashpoint of 23°C c.c. or less in regulation II-2/19 of SOLAS, 74, as amended.

MFAG-No : 127

IATA

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) Y344 PCA limited quantity max net quantity (IATA) 10L 355 PCA packing instructions (IATA) 60L PCA max net quantity (IATA) : 366 CAO packing instructions (IATA) CAO max net quantity (IATA) 220L Special provision (IATA) A9, A58 ERG code (IATA) 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

10/3/2024 (Issue date) EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
ethanol, ethyl alcohol	64-17-5	Present	Active	

15.2. International regulations

No additional information available

15.3. US State regulations

Component	State or local regulations
ethanol, ethyl alcohol(64-17-5)	U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S New York City - Right to Know Hazardous Substances List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources

: ECHA (European Chemicals Agency).

Other information

REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation

Abbreviations and acronyms	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
LC50	Median lethal concentration
LD50	Median lethal dose
SDS	Safety Data Sheet
CAS	CAS (Chemical Abstracts Service) number
EG-nr	EINECS- en ELINCS-number
EINECS	European Inventory of Existing Commercial Substances
GHS	GHS: Globally Harmonized System of Classification and Labelling of Chemicals


NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can

be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions.

Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well

as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)858881927 | info@chemprosbv.nl